

## TECHNICAL DATA SHEET



# SYNTHETIC SAE 10W-30

**PRODUCT # 10050, 10117, 10118, 10119, 10128**  
**API Service SM/SL/SJ/CF**

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>33.2</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.8591</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.153</b>
<b>Viscosity @ 40°C</b>	<b>D-445</b>	<b>57.0</b>
<b>Viscosity @ 100°C</b>	<b>D-445</b>	<b>10.5</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>178</b>
<b>Color</b>		<b>Light Brown</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>455</b>
<b>Pour Point, °C</b>	<b>D-97</b>	<b>-36</b>

**This excellent product provides the consistent viscosity needed for precision ET racing. Lucas Synthetic SAE 10W-30 is a formulation of only the finest light synthetic base oils plus an exclusive additive package that includes lubricity agents and anti-seize agents that control drag like a zero weight oil and protect like a heavy multi-viscosity oil.**

**It's the perfect non-foaming lubricant for high RPM go-cart and motorcycle engines.**

**It's also excellent for normal highway use.**

**Lucas Synthetic SAE 10W-30 is the perfect lubricant for extreme low temperatures or extreme high temperatures and blends with other synthetic or regular motor oil. Blend a quart or two into your conventional motor oil for easier starting and longer oil life.**

**Meets or exceeds all manufacturers specifications for SAE10W-30 and API SL and ILSAC GF3. Exceeds A3/B3/B4 • SM/SL/SJ/CF.**

**Exceeds American and European OEM specifications, exceeds performance levels of API SM/SL/SJ/CF • ACEA A3-98, B3-98, B4-98 • VW 500/502/505 • Daimler Chrysler 229.1 • BMW Longlife Oil.**